



Increase your performance and flexibility with the highly configurable RIU-200.



The GE Aviation RIU-200 is a highly flexible and configurable remote interface unit (RIU). Forming an integral part of GE's successful RIU Product Family, the RIU-200 offers a near "off-the-shelf" solution to a wide range of applications including:

- Distributed input/output (I/O)
- Centralised I/O
- Sub-system control (embedded or as a stand-alone unit)

In a compact package measuring only 8.5 x 8.5 x 1.1 inches, the RIU-200 provides 200 interface channels combined with either:

- a dual redundant MIL-STD-1553B Remote Terminal, or
- an ARINC 429 (2 Tx and 4 Rx channels) databus interface

Flexibility and configurability

A micro-controller based I/O core forms the heart of the system that provides a range of highly flexible generic interface channels designed to suit most common vehicle systems applications. Each interface can be configured for different applications by the use of data tables; specifically developed for each new application, these data tables invoke built-in generic software and hardware functionality.

Low cost

The unit's inherent flexibility allows:

- development costs and timescales to be minimised
- design changes to be quickly and easily implemented

With the capability to accommodate multiple data tables selectable through external configuration pins, a single part number can be used to cover multiple applications, thus reducing cost of ownership.

High reliability and maintainability

The robust and ruggedised RIU Product Family offers a high-level of reliability, with a typical Mean Time Between Failures (MTBF) of 100,000 hours. Incorporating a comprehensive built-in test capability, RIUs can detect internal unit faults, and additionally detect faults within the sensors and wiring to which they are connected. Maintenance improvements are realised through the ability to utilise a single part to perform multiple applications, simplifying maintenance procedures and reducing spares inventories.

Optimised design approach

By embracing a technology re-use philosophy, the RIU-200, like all products within the RIU Product Family, utilises a common set of technology building blocks. This approach enables 'mature' and 'de-risked' solutions. A further key innovation that reduces GE's development timescales is the Requirement Capture Tool (RCT), specifically developed by GE to support its development activities for the RIU Product Family. This provides the capability to capture the specific interfacing requirements of the customer and to efficiently transpose these onto the highly flexible software architecture.

Customisation

The unit is designed with a pre-defined set of generic interfaces, chosen to suit a wide range of common aircraft sensors and effectors. Bespoke solutions with more specialised or a different mix of interfaces that provide a cost effective and weight optimised solution can be developed from the library of solutions already available and within the timescales associated with the development of the application's configuration data.

Key Features

- Provides 200 channels of flexible I/O
- Low lifecycle cost
- Low weight, volume and power consumption
- Ruggedised for harsh/remote environments
- Voltage/current/resistance/frequency/pulse-width modulation (PWM)/discrete input and output capability
- Configurable by PC downloadable data tables without requiring software re-design
- Available with either:
 - a dual redundant MIL-STD-1553B Remote Terminal, or
 - an ARINC 429 (2 Tx and 4 Rx channels) databus interface
- Optimised for control/monitoring of VMS sub-systems, including electrical, fuel, hydraulics, environmental control, brakes, health monitoring, etc.
- Can perform local control loop closure
- Can be easily adapted for more specialised interfaces
- Designed to interface, as standard to a wide range of aircraft sensors and effectors including:
 - micro-switches
 - active sensors, low voltage d.c., frequency or pulse-width modulated signals
 - resistive sensors, e.g., PRT, thermistor, etc.
 - thermocouples
 - L/RVDT
 - d.c. bus voltage monitors
 - a.c. bus voltage, current monitors
 - potentiometers
 - strain gauges
 - tachometers
 - synchro/resolver
 - solenoid valves
 - relays and contactors
 - solid-state power controllers
 - active servos
- CAN bus available on request

By embracing a technology re-use philosophy the RIU-200, like all products within the RIU Product Family, utilises a common set of technology building blocks. This approach enables ‘mature’ and ‘de-risked’ solutions.

Specifications - RIU-200

Test	Specification
Temperature	MIL-STD-810F, method 520.2, proc. III, (-45 to +71 °C operating)
Altitude	MIL-STD-810F, method 520.2, proc. III, (3.14 – 15.67 psia)
Shock	MIL-STD-810F, method 516.5, proc. I and V, (40 g peak for 11 ms, crash safety)
Vibration	MIL-STD-810F, method 514.5, proc. I
Humidity	MIL-STD-810F, method 507.4
Salt fog	MIL-STD-810F, method 509.4 and RTCA/DO-160D, sect. 14, cat S (35 °C 48 hrs exposure, 48 hrs drying)
Sand and dust	MIL-STD-810F, method 510.4, procedure I (blowing dust)
Fungus	MIL-STD-810F, method 508.5
Waterproofness	MIL-STD-810F, method 506.2, procedure I (driving rain)
Fluid susceptibility	MIL-STD-810F, method 504 and RTCA/DO-160D
EMC	MIL-STD-461E, CE101, CE102, CS101, CS114, CS115, CS116, RS103, RE102, RTCA/DO-160D Section 22 change 3 and Section 21

Power	28 V d.c. to RTCA/DO-160D, sect. 16, change 2, cat. B
Consumption	5 W
Dimensions	8.5 x 8.5 x 1.1 in (216 x 216 x 28 mm, excluding connectors)
Weight	2.8 lb (1.27 kg)

Available with either:		
ARINC 429 Tx/Rx	I	4
	O	2
MIL-STD-1553B dual redundant remote terminal	I/O	1

I/O configurations and quantities

Interface type	I/O	Quantity
Frequency/PWM/discrete	I	70
(Diff.) frequency/PWM/voltage/discrete	I	28
Frequency/speed	I	3
Voltage/discrete	I	28
(Diff.) Voltage/discrete	I	14
Synchro/resolver/L/RVDT	I	8
a.c. Voltage/discrete	I	8
a.c. Current transformer	I	4
Ground switch 0.5A discrete	O	18
Ground switch 0.5A discrete/frequency/PWM	O	2
Voltage 0-10 V	O	2
RS-485	I/O	1



GE Aviation
 Bishops Cleeve
 Cheltenham
 Gloucestershire
 GL52 8SF, UK
 +44 (0)1242 673333
 www.geaviation.com

The information contained in this document is GE Aviation Systems Ltd. proprietary information and is disclosed in confidence. It is the property of GE Aviation Systems LLC. and shall not be used, disclosed to others or reproduced without the express written consent of GE Aviation Systems LLC. including, but without limitation, it is not to be used in the creation, manufacture, development, or derivation of any repairs, modifications, spare parts, designs, or configuration changes or to obtain FAA or any other government or regulatory approval to do so. If consent is given for reproduction in whole or in part, this notice and the notice set forth on each page of this document shall appear in any such reproduction in whole or in part.